

D/A3185

AMENDMENT(S) TO THE CLAIMS

This listing of claims will replace all prior versions, and listings, of claims in the application.

Listing of Claims:

1. - 13. (canceled)
14. (original) A drop generator comprising:
 - a pressure chamber;
 - an inlet channel connected to the pressure chamber;
 - an outlet channel connected to the pressure chamber;
 - the outlet channel including a first circular outlet channel section connected to the pressure chamber, a first non-circular outlet channel section connected to the first circular outlet channel section, a second circular outlet channel section connected to the first non-circular outlet channel section, and a second non-circular outlet channel section connected to the second circular outlet section; and
 - a drop emitting nozzle disposed at an end of the second non-circular outlet channel.
15. (original) The drop generator of claim 14 further including a piezoelectric element.
16. (original) The drop generator of claim 14 wherein the inlet channel receives melted solid ink.

BEST AVAILABLE COPY

D/A3185

17. (original) The drop generator of claim 14 wherein at least one of the first circular section and the second circular section includes a first circular sub-section and a second circular sub-section.

18. (original) The drop generator of claim 14 wherein the first non-circular section has an oval cross-section.

19. (original) The drop generator of claim 14 wherein the non-circular section has a generally egg-shaped cross-section.

20. (original) The drop generator of claim 14 wherein the non-circular section has a generally egg-shaped cross-section, and wherein the nozzle is disposed at a smaller end of the egg-shaped cross-section.

21. (original) The drop generator of claim 14 wherein the nozzle is disposed at an end of the non-circular section.

22. (original) The drop generator of claim 14 wherein the ink pressure chamber has a cross-section that is generally parallelogram shaped.

23. (original) The drop generator of claim 14 wherein the nozzle emits drops having a mass in the range of about 20 nanograms to about 30 nanograms.

24. (original) The drop generator of claim 14 wherein the pressure chamber is operated at a frequency of about 23 KHz to about 30 KHz.

D/A3185

25. (original) The drop generator of claim 14 wherein the outlet channel has a length in the range of about 59/1000 inches to about 79/1000 inches.

26. (original) The drop generator of claim 14 wherein the outlet channel has a length in the range of about 69/1000 inches to about 77/1000 inches.

27. (original) The drop generator of claim 14 wherein the first circular outlet channel section has a length that is less than about 20/1000 inches.

28. (original) The drop generator of claim 14 wherein the first circular outlet channel section has a length in range of about 11/1000 inches to about 13/1000 inches.

29. (original) The drop generator of claim 14 wherein the second circular outlet channel section has a length that is less than about 40/1000 inches.

30. (original) The drop generator of claim 14 wherein the second circular outlet channel section has a length in the range of about 24/1000 inches to about 26/1000 inches.

31. (original) The drop generator of claim 14 wherein the first circular outlet channel section has an average diameter in the range of about 10/1000 inches to about 20/1000 inches.

D/A3185

32. (original) The drop generator of claim 14 wherein the first circular outlet channel section has an average diameter in the range of about 11/1000 inches to about 13/1000 inches.

33. (original) The drop generator of claim 14 wherein the second circular outlet channel section has an average diameter in the range of about 8/1000 inches to about 15/1000 inches.

34. (original) The drop generator of claim 14 wherein the second circular outlet channel section has an average diameter in the range of about 12/1000 inches to about 14/1000 inches.

35. (original) The drop generator of claim 14 wherein the first non-circular outlet channel section has a length that is less than about 40/1000 inches.

36. (original) The drop generator of claim 14 wherein the first non-circular outlet channel section has a length in the range of about 27/1000 inches to about 29/1000 inches.

37. (original) The drop generator of claim 14 wherein the second non-circular outlet channel section has a length in the range of about 4/1000 inches to about 10/1000 inches.

38. (original) The drop generator of claim 14 wherein the second non-circular outlet channel section has a length in the range of about 7/1000 inches to about 9/1000 inches.

D/A3185

39. (original) The drop generator of claim 14 wherein the first non-circular outlet channel section has an effective diameter of about 10/1000 inches to about 20/1000 inches.

40. (original) The drop generator of claim 14 wherein the first non-circular outlet channel section has an effective diameter of about 15/1000 inches to about 17/1000 inches.

41. (original) The drop generator of claim 14 wherein the second non-circular outlet channel section has an effective diameter of about 8/1000 inches to about 16/1000 inches.

42. (original) The drop generator of claim 14 wherein the second non-circular outlet channel section has an effective diameter of about 13/1000 inches to about 16/1000 inches.

43. (original) A drop generator comprising:
a pressure chamber;
an inlet channel connected to the pressure chamber;
an outlet channel connected to the pressure chamber, the outlet channel having an outlet channel axis;

the outlet channel including a first circular outlet channel section connected to the pressure chamber, a first non-circular outlet channel section connected to the first circular outlet channel section, a second circular outlet channel section connected to the first non-circular outlet channel section, and a second non-circular outlet channel section connected to the second circular outlet section;

D/A3185

wherein the first circular outlet channel section, the first non-circular outlet channel section, and the second circular outlet channel section are substantially centered on the outlet channel axis; and

a nozzle disposed at an end of the second non-circular outlet channel section and offset from the outlet channel axis.

44. (presently amended) The drop generator of claim 43 wherein the second non-circular outlet channel section ~~non-circular section~~ has a generally egg-shaped cross-section.

45. (original) The drop generator of claim 43 wherein the first circular outlet channel section includes a plurality of circular sub-sections.

46. (original) The drop generator of claim 43 wherein the second circular outlet channel section includes a plurality of circular sub-sections.

47. (original) The drop generator of claim 43 wherein the ink pressure chamber has a cross-section that is generally parallelogram shaped.

48. (original) The drop generator of claim 43 wherein the nozzle emits drops having a mass in the range of about 20 nanograms to about 30 nanograms.

49. (original) The drop generator of claim 43 wherein the pressure chamber is operated at a frequency of about 23 KHz to about 30 KHz.

50. (new) A drop generator comprising:
a pressure chamber;

D/A3185

an inlet channel connected to the pressure chamber;
an outlet channel connected to the pressure chamber, the outlet
channel having an outlet channel axis;
a drop emitting nozzle disposed at an end of the outlet channel;
and

the outlet channel including a circular outlet channel section and a
non-circular outlet channel section having an oval cross-section.

51. (new) A drop generator comprising:
a pressure chamber;
an inlet channel connected to the pressure chamber;
an outlet channel connected to the pressure chamber, the outlet
channel having an outlet channel axis;
a drop emitting nozzle disposed at an end of the outlet channel;
and

the outlet channel including a circular outlet channel section and a
non-circular outlet channel section having a generally egg-shaped cross-
section.

52. (new) The drop generator of claim 51 wherein the nozzle is
disposed at a smaller end of the egg-shaped cross-section.

53. (new) A drop generator comprising:
a pressure chamber;
an inlet channel connected to the pressure chamber;
an outlet channel connected to the pressure chamber, the outlet
channel having an outlet channel axis;

D/A3185

a drop emitting nozzle disposed at an end of the outlet channel, wherein the nozzle emits drops having a mass in the range of about 20 nanograms to about 30 nanograms; and

the outlet channel including a circular outlet channel section and a non-circular outlet channel section.

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ **BLACK BORDERS**
- ☐ **IMAGE CUT OFF AT TOP, BOTTOM OR SIDES**
- ☐ **FADED TEXT OR DRAWING**
- ☐ **BLURRED OR ILLEGIBLE TEXT OR DRAWING**
- ☐ **SKEWED/SLANTED IMAGES**
- ☐ **COLOR OR BLACK AND WHITE PHOTOGRAPHS**
- ☐ **GRAY SCALE DOCUMENTS**
- ☒ **LINES OR MARKS ON ORIGINAL DOCUMENT**
- ☐ **REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY**
- ☐ **OTHER:** _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.